

# Corning® Water Testing Product Selection Guide

CORNING



# Water Testing

US EPA regulations require the testing of discharges into surface waters including rivers, lakes, wetlands, estuaries, and oceans. The major categories of laboratory tests include organics, solids, nutrients, and physical properties (e.g., temperature, color, pH, turbidity, odor), as well as microbial indicators.

Corning provides a range of equipment and disposable and reusable laboratory supplies for compliance testing including a full range of PYREX® glassware—the leading brand of laboratory glassware for more than 100 years.

Our PYREX products include every day lab tools, such as beakers and graduated cylinders, as well as specialized items such as PYREX flasks designed for Kjeldahl digestions, desiccators, distillation glassware, and bottles for Biochemical Oxygen Demand (BOD) testing.

In addition, we offer a full range of Corning® Gosselin™ microbiological consumables to test for bacterial indicators prior to wastewater discharge, as well as a full range of benchtop equipment including Corning hot plates and stirrers, incubators, water baths, compact centrifuges, and more.

To see the full line of Corning equipment and supplies, visit [www.corning.com/lifesciences](http://www.corning.com/lifesciences).

	Workflow					
	S	P	T	A	D	
	Sampling	Preparation	Testing	Analysis	Disposal	Page No(s).
Water Sampling Bottle	■					2
Storage Bottles	■	■	■	■		3
Autoclavable Bottles	■	■	■			4
Equipment <i>Centrifugation, Constant Temperature, Agitation</i>		■				5 - 9
Liquid Handling <i>Pipet Controllers, Pipettors, Serological Pipet, Hand-held Pipet Tips (plastic, glass)</i>		■	■			10 - 12
Flasks (glass) <i>Vacuum/Filtering, Volumetric, Erlenmeyer</i>		■	■			13
<i>Kjeldahl</i>			■			13
Graduated Cylinder (glass)		■	■			14
Biochemical Oxygen Demand (BOD) Bottles (glass)		■	■			14
Beaker (glass)		■	■			14
Centrifugation and Storage <i>Centrifuge Tubes, Microcentrifuge Tubes</i>		■	■	■		15 - 16
Additional Glassware <i>Desiccator, Fritted Disc (Gooch Type), Distillation Apparatus, Filter Funnels, Burets</i>			■			17
Petri Dishes <i>Glass, Plastic</i>			■	■		18
Inoculating Loops			■	■		19
Autoclave Bags					■	20

## Water Sampling Bottle



### Corning® Gosselin™ Water Sample Collection Bottle, Square Polyethylene, PET

Cat. No.	Description	Qty/Pk	Qty/Cs
83-HP250B-55	250 mL square, PET, 34.7 mm tamper-evident screw cap, contains 160 mg/L dosage of sodium thiosulfate, sterile	24	144

# Storage Bottles



## Corning® Polystyrene (PS) Storage Bottles

### Corning Low Profile Easy Grip Style

Cat. No.	Volume	Neck size (mm)	Qty/Pk	Qty/Cs
83-431175	150 mL	45	2	24
83-430281	250 mL	45	2	24
83-430282	500 mL	45	2	24
83-430518	1L	45	2	24



## Corning Square Polycarbonate (PC) Storage Bottles

Cat. No.	Volume	Bottle Shape	Material	Neck Diam. (mm)	Qty/Bag	Qty/Cs
83-431430	150 mL	Square	PC	45	1	24
83-431431	250 mL	Square	PC	45	1	24
83-431432	500 mL	Square	PC	45	1	24
83-431433	1L	Square	PC	45	1	24



## Corning Gosselin™ Wide Mouth HDPE Bottles

Cat. No.	Description	Qty/Cs
83-LR50A-18	50 mL, 27 mm red screw cap, sterile	600
83-LR100-12	100 mL, 37 mm red screw cap, sterile	335
83-LR150A-14	150 mL, 37 mm red screw cap with natural seal, sterile	250
83-LR250-09	250 mL, 37 mm red screw cap, sterile	145
83-LR500-04	500 mL, 58 mm red screw cap, sterile	140
83-LR1000-08	1L, 58 mm red screw cap, sterile	68

## Autoclavable Bottles



### PYREX® Bottle, Solution

Cat. No.	Approx. Capacity (mL)	Rubber Stopper No.	Approx. O.D. x Height (mm)	Qty/Cs
1-1595-5	19,000	12	292 x 508	1



### PYREX Bottle, Media, Storage, Screw Cap

Cat. No.	Approx. Capacity (mL)	Thread Finish	Approx. O.D. x Height (mm)	Grad. Range (mL)	Grad. Increment (mL)	Qty/Cs
1-1395-250	250	GL 45	70 x 138	50-200	50	10



# Equipment



## Corning® LSE™ Mini Microcentrifuge

Cat. No.	Description	Voltage	Speed (rpm)	Dimensions (H x W x D)	Qty/Cs
83-6770	LSE mini microcentrifuge	115V, 60Hz	6,000	6 x 6 in. (153 mm x 153 mm)	1

Accessories included with Cat. No. 6770 and also sold separately:

Cat. No.	Description	Qty/Pk
83-6770-RT	Rotor, holds 8 x 1.5/2.0 mL tubes	1
83-6770-RTS	Rotor, holds 4 x 8-strip tubes	1
83-6770-RTA.20	Adapter, 0.20 for rotor (Cat. No. 6770-RT)	8
83-6770-RTA.25	Adapter, 0.25 for rotor (Cat. No. 6770-RT)	8
83-6770-RTA.5	Adapter, 0.5 for rotor (Cat. No. 6770-RT)	8



## Corning LSE™ High Speed Microcentrifuge

Cat. No.	Description	Voltage	Plug Type	Speed (rpm)	Weight	Dimensions (H x W x D)	Qty/Cs
1-6765-HS	LSE high speed microcentrifuge	120V, 50/60Hz	US	500 - 13,300	18 lbs. (8.1 kg)	9.25 x 11.5 x 8.5 in. (23.5 x 29.3 x 21.6 cm)	1



## Corning LSE™ Compact Centrifuge

Cat. No.	Description	Voltage	Plug Type	Speed (rpm)	Weight	Dimensions (L x W x D)	Qty/Cs
1-6755	LSE compact centrifuge	120V, 50/60Hz	US	200 - 6,000	33 lbs. (15 kg)	11 x 14.6 x 10.2 in. (28 x 37 x 26 cm)	1

### Rotors

Cat. No.	Description	Max. Speed (rpm)	Max. RCF	Qty/Cs
1-480136	LSE 6 x 50 mL fixed angle rotor	6,000	3,820	1
1-480137	LSE 12 x 15 mL fixed angle rotor	6,000	4,180	1
1-480138	LSE 6 x 5 mL swing-out rotor	3,500	1,450	1
1-480139	LSE 18 x 1.5 mL fixed angle rotor	6,000	2,930	1
1-480143	LSE combination rotor for 5, 15, and 50 mL tubes	6,000	3,820	1

### Adapters

Cat. No.	Description	Qty/Cs
1-480140	LSE adapters for 10 and 15 mL tubes in 50 mL rotor	6
1-480141	LSE adapters for 5 and 7 mL tubes in 50 mL rotor	6
1-480142	LSE adapters for 5, 7, and 10 mL tubes in 15 mL rotor	6



6 x 50 mL fixed angle rotor  
(Cat. No. 480136)



12 x 15 mL fixed angle rotor  
(Cat. No. 480137)



6 x 5 mL swing-out rotor  
(Cat. No. 480138)



18 x 1.5 mL fixed angle rotor  
(Cat. No. 480139)




Combination rotor  
(Cat. No. 480143)



### Corning® LSE™ 6 Liter Digital Water Bath

Cat. No.	Description	Temperature Range	Weight	Dimensions (H x W x D)	Qty/Cs
1-6783	Digital water bath, 6L, 120V	Ambient +5°C to 99°C	19 lbs. (8.6 kg)	14.9 x 11.4 x 9.0 in. (12.9 in. w/cover) 38 x 29 x 23 cm (33 cm w/cover)	1



### Corning LSE Digital Dry Bath Heater

Cat. No.	Description	Block Capacity	Voltage Plug	Weight	Dimensions (L x W x H)	Qty/Cs
1-6875-SB	LSE digital dry bath heater	Single	120V US	7.0 lbs. (3.2 kg)	8.3 x 12.4 x 4.7 in. (21 x 29 x 12 cm)	1

#### Accessories

Cat. No.	Description	Qty/Cs
1-480117	Single block, 20 x 2.0 mL tubes	1
1-480119	Single block, 24 x 1.5 mL tubes	1
1-480124	Single block, 12 x 15 mL centrifuge tubes	1
1-480129	Single block, 5 x 50 mL centrifuge tubes (for single block unit only)	1



### Corning Digital Stirring Hot Plate

Cat. No.	Model	Voltage	Temperature/ Stir Range (rpm)	Dimensions (W x D x H)	Qty/Cs
1-6795-420D	PC-420D	120V/60Hz	5°C - 550°C/60 - 1,150	4.3 x 7.7 x 11 in. (10.8 x 19.7 x 28 cm)	1

## Corning LSE Benchtop Shaking Incubator



Cat. No.	Description	Voltage	Operation Temperature Range	Dimensions (L x W x D)	Qty/Cs
1-6790	LSE Benchtop shaking incubator with platform	120V	4°C to 65°C	14.6 x 20.9 x 15.7 in. (37 x 53 x 40 cm)	1

### Accessories

Cat. No.	Description	Qty/Cs
1-480144	Universal platform, 30 x 30 cm	1
1-480145	Petri dish shelf	1
1-480146	Sticky mat, 150 x 150 x 30 mm	1
1-480147	Microtiter hotel, holds maximum 3 microplates	1
1-480148	Combination tube holder, 6 x 15/50 mL tubes	1
1-480149	Plastic clamp, 125 mL	1
1-480150	Plastic clamp, 250 mL	1
1-480151	Plastic clamp, 500 mL	1
1-480152	Plastic clamp, 1000 mL	1

## Corning® LSE™ 49L Shaking Incubator



Cat. No.	Description	Voltage	Operation Temperature Range	Shaker Speed (rpm)	Weight	Dimensions (L x W x D)	Qty/Cs
1-6750	LSE Shaking incubator, 49 Liters	120V	Ambient +5°C to 80°C	20 to 400 (300 when stacked)	83 lbs. (37.7 kg)	3 x 19.25 x 22.25 in. (42.5 x 55 x 58 cm)	1

### Accessories

Cat. No.	Description	Qty/Cs
1-480153	Flask clamp platform, pre-drilled	1
1-480154	Flat platform with nonslip rubber mat (300 x 300 mm)	1
1-480155	Double flat platform with non-slip rubber mat (300 x 300 mm)	1
1-480156	Universal spring-loaded clamp platform for Cat. No. 6750	1
1-480157	Shelf, full, for Cat. No. 6750	1
1-480158	Stacking adapter for Cat. No. 6750	1

## Corning LSE 71L Shaking Incubator



Cat. No.	Description	Voltage	Operation Temperature Range	Shaker Speed (rpm)	Weight	Dimensions (L x W x D)	Qty/Cs
1-6753	LSE Shaking incubator, 71 Liters	120V	Ambient +5°C to 80°C	20 - 300	140 lbs. (63.6 kg)	22.6 x 21.4 x 25 in. (57.4 x 54.4 x 63.5 cm)	1

### Accessories

Cat. No.	Description	Qty/Cs
1-480159	Shaking platform pre-drilled for flask clamps	1
1-480160	Flat shaker platform with non-slip rubber mat (390 x 330 mm)	1
1-480161	Platform with 4 x 2L flask clamps	1
1-480162	Platform with 6 x 1L flask clamps	1
1-480163	Platform with 8 x 500 mL flask clamps	1
1-480164	Platform with 12 x 250 mL flask clamps	1
1-480165	Platform with 20 x 125 mL flask clamps	1
1-480166	Platform with 30 x 50 mL flask clamps	1
1-480168	Rack holder for 15 mL test tubes	1
1-480169	Rack holder for 50 mL test tubes	1
1-480170	Shelf, full, for Cat. No. 6753	1





### Corning® LSE™ Vortex Mixer

Cat. No.	Description	Voltage	Plug Type	Speed (rpm)	Weight	Dimensions (L x W x D)	Qty/Cs
1-6775	LSE vortex mixer	120V, 50/60Hz	US	0 - 3,400	4.8 lbs. (2.2 kg)	5.5 x 6.3 x 5.1 in. (14 x 16 x 13 cm)	1

#### Accessories

Cat. No.	Description	Qty/Cs
1-480100	Optional head, 3 inch, for processing larger numbers of tubes	1
1-480101	Optional head for 24 x 1.5/ 2.0 mL tubes, 24 x 0.5 mL tubes, and 32 x 0.2 mL tubes (or 4 tube strips)	1
1-480103	Optional head for 8 x 15 mL and 8 x 12/13 mm diameter tubes	1
1-480104	Optional head attachment for 6 x 50 mL tubes	1
1-480105	Optional head for 12 x 1.5/2.0 mL tubes, held horizontally	1
1-480106	Optional head for 4 x 15 mL tubes, held horizontally	1
1-480107	Optional head for 2 x 50 mL tubes, held horizontally	1



### Corning LSE Low Speed Orbital Shaker

Cat. No.	Description	Voltage	Plug Type	Speed (rpm)	Weight	Dimensions (L x W x D)	Qty/Cs
1-6780-FP	LSE low speed orbital shaker	120V, 50/60Hz	US	3 - 60	11 lbs. (5 kg)	10 x 12.6 x 6.3 in. (25.5 x 32 x 16 cm)	1



### Corning LSE Platform Rockers

Cat. No.	Description	Platform	Voltage	Speed (Tilts/min.)	Weight	Dimensions (L x W x H)	Qty/Cs
1-6703	LSE platform rocker	Single	115V, 50/60Hz	5 - 120	11.7 lbs. (5.3 kg)	12.8 x 14.2 x 5.7 in. (32.5 x 36 x 14.5 cm)	1
1-6705	LSE platform rocker	Double	115V, 50/60Hz	5 - 120	12.7 lbs. (5.8 kg)	12.8 x 14.2 x 5.7 in. (32.5 x 36 x 14.5 cm)	1





## Corning® LSE™ Digital Vortexer

Cat. No.	Description	Voltage	Speed (rpm)	Weight	Dimensions (L x W x H)	Qty/Cs
1-6709	LSE digital vortexer	115V/60Hz	100 - 1,200	4.4 lbs. (2 kg)	10.3 x 13.3 x 5.1 in. (26.2 x 33.7 x 13 cm)	1

### Accessories

Cat. No.	Description	Qty/Cs
1-48010	Platform for four microplates	1
1-48012	Spring-loaded platform for flasks, bottles, or tube racks	1




# Liquid Handling



## Corning® Stripettor™ Ultra Pipet Controller

Cat. No.	Description	Qty/Cs
83-4099	Corning Stripettor Ultra pipet controller	1



## Stripette™ Serological Pipets

### Individually Wrapped, Paper/Plastic Wrap

Cat. No.	Capacity (mL)	Graduations (mL)	Negative Grads. (mL)	Color-coded Stripe	Qty/Pk	Qty/Cs
83-4485	1	1/100	0.2	Yellow	50	1,000
83-4486	2	1/100	0.2	Green	50	1,000
83-4487	5	1/10	2.5	Blue	50	200
83-4488	10	1/10	3.0	Orange	50	200
83-4489	25	2/10	10.0	Red	25	200
83-4490	50	1/2	10.0	Purple	25	100
83-4491	100	1	n/a	Aqua	10	100


### Individually Wrapped, Clear Plastic Wrap

83-4011	1	1/100	0.2	Yellow	100	1,000
83-4012	1	1/100	0.2	Yellow	100	200
83-4021	2	1/100	0.2	Green	100	1,000
83-4051	5	1/10	2.5	Blue	50	200
83-4101	10	1/10	3.0	Orange	50	200
83-4492*	10	1/10	3.0	Orange	50	200
83-4251	25	2/10	10.0	Red	50	200
83-4501	50	1/2	10.0	Purple	25	100
83-4484	100	1	n/a	Aqua	10	100

### Bulk Packed in Bags

83-4010	1	1/100	0.2	Yellow	50	1,000
83-4020	2	1/100	0.2	Green	50	1,000
83-4050	5	1/10	2.5	Blue	50	500
83-4100	10	1/10	3.0	Orange	50	500
83-4250	25	2/10	10.0	Red	25	200
83-4500	50	1/2	10.0	Purple	25	100

\*Cat. No. 4492 features a wide tip for handling viscous fluids.



For Falcon® serological pipets, visit [www.corning.com/lifesciences](http://www.corning.com/lifesciences).



### PYREX® Pipet, Reusable Glass Serological, Color-coded, Colored Markings, To Deliver

Cat. No.	Approx. Capacity (mL)	Tolerance (± mL)	Grad. Increment (mL)	Approx. O.D. x Length (mm)	Qty/Pk	Qty/Cs
1-7085-2	2.0	.02	.1	7 x 350	6	12
1-7085-5	5.0	.04	.1	8 x 350	6	12
1-7085-10	10.0	.06	.1	10 x 350	—	12

Do not pipet by mouth. We suggest using a mechanical pipetting device. Reference: ASTM E-1044.



### Corning® Step-R™ Starter Pack

Cat. No.	Description	Qty/Cs
83-6636	Corning Step-R starter pack Contains: Corning Step-R Repeating Pipettor (Cat. No. 4217); Adapter for 25 mL syringe tips (Cat. No. 4218) and 50 mL syringe tips (Cat. No. 4219); Syringe tips (5/pk) of 0.05 mL (Cat. No. 6620); 2.5 mL (Cat. No. 6623), 5 mL (Cat. No. 6624), 12.5 mL (Cat. No. 6625); Syringe tips (2/pk) of 25 mL (Cat. No. 6626), and 50 mL (Cat. No. 6627)	1 kit



### Corning Syringe Tips

Syringe Tip	Cat. No. Non-sterile	Cat. No. Sterile	Qty/Cs
0.05 mL	83-6620	83-6628	100
0.5 mL	83-6621	83-6629	100
1.25 mL	83-6622	83-6630	100
2.5 mL	83-6623	83-6631	100
5 mL	83-6624	83-6632	100
12.5 mL	83-6625	83-6633	100
55 mL	83-6626	83-6634	25
50 mL	83-6627	83-6635	25



### Corning Lambda™ Plus Starter Kit

Cat. No.	Description	Qty/Cs
83-4069	Lambda Plus starter kit Contains: Lambda Plus single-channel pipettor, 0.5 to 10 µL (Cat. No. 4071); Lambda Plus single-channel pipettor, 2 to 20 µL (Cat. No. 4072); Lambda Plus single-channel pipettor, 20 to 200 µL (Cat. No. 4074); Lambda Plus single-channel pipettor, 100 to 1000 µL (Cat. No. 4075); Universal carousel rack for six single-channel pipettors (Cat. No. 4078); Corning DeckWorks Pipet Tips: 10 µL (Cat. No. 4135), 200 µL (Cat. No. 4138), and 1000 µL (Cat. No. 4140)	1 kit



## Corning® DeckWorks Reload Systems

### Standard Tips

Cat. No.	Volume Range (µL)	Color	Sterile	Decks/Pk	Tips/Pk	Pk/Cs
83-4125	0.1 - 10	Natural	No	10	960	4
83-4126	1 - 200	Natural	No	10	960	4
83-4128	1 - 300	Natural	No	10	960	4
83-4129	100 - 1,000	Natural	No	8	768	4

### Low Binding Tips

83-4153	0.1 - 10	Natural	No	10	960	4
83-4154	1 - 200	Natural	No	10	960	4
83-4155	1 - 300	Natural	No	10	960	4



## Corning DeckWorks Hinged Rack Pipet Tips

### Low Binding Tips

Cat. No.	Volume Range (µL)	Color	Sterile	Racks/Pk	Tips/Pk	Pk/Cs
83-4150	0.1 - 10	Natural	Yes	10	960	4
83-4147	0.1 - 10	Natural	No	10	960	4
83-4151	1 - 200	Natural	Yes	10	960	4
83-4148	1 - 200	Natural	No	10	960	4
83-4152	1 - 300	Natural	Yes	10	960	4
83-4149	1 - 300	Natural	No	10	960	4

### Low Binding Barrier Tips

Cat. No.	Volume Range (µL)	Color	Sterile	Racks/Pk	Tips/Pk	Pk/Cs
83-4135	0.1 - 10	Natural	Yes	10	960	4
83-4136	1 - 20	Natural	Yes	10	960	4
83-4137	1 - 100	Natural	Yes	10	960	4
83-4138	1 - 200	Natural	Yes	10	960	4
83-4140	100 - 1,000	Natural	Yes	8	768	4


## Corning DeckWorks Tip Station

Cat. No.	Volume Range (µL)	Color	Sterile	Tips/Pk	Pk/Cs
83-4141	0.1 - 10	Natural	No	960	5
83-4143	0.1 - 10	Natural	Yes	960	5
83-4142	1 - 200	Natural	No	960	5
83-4144	1 - 200	Natural	Yes	960	5





## Flasks



### PYREX® Flask, Filtering, Heavy Wall, Tubulation, Graduated

Cat. No.	Approx. Capacity (mL)	Grad. Range (mL)	Grad. Increment (mL)	Rubber Stopper No.	Approx. O.D. x Height (mm)	Qty/Pk	Qty/Cs
1-5340-500	500	150 - 500	50	7	106 x 184	6	18



### PYREX Flask, Volumetric, Class A, PYREX § Stopper

Cat. No.	Description	Capacity (mL)	Tol. (± mL)	Approx. O.D. x Height (mm)	Stopper No.	Qty/Pk	Qty/Cs
1-5640-100	Complete	100	0.08	60 x 181	13	6	12
1-5640-500	Complete	500	0.20	99 x 287	19	6	12
1-5640-1L	Complete	1000	0.30	127 x 346	22	1	6



### PYREX Flask, Erlenmeyer, Narrow Mouth, Heavy Duty Rim, Graduated

Cat. No.	Approx. Capacity (mL)	Rubber Stopper No.	Grad. Range (mL)	Grad. Increment (mL)	Approx. O.D. x Height (mm)	Qty/Pk	Qty/Cs
1-4980-125	125	5	50 - 125	25	67 x 114	12	48
1-4980-500	500	7	100 - 500	50	101 x 176	6	3



### PYREX Flask, Kjeldahl, Round Bottom, Long Neck

Cat. No.	Approx. Capacity (mL)	Rubber Stopper No.	Approx. O.D. x Height (mm)	Qty/Pk	Qty/Cs
1-5420-500	500	6	101 x 324	6	24

## Graduated Cylinder



### PYREX® Cylinder, Single Metric Scale, Graduated, To Contain

Cat. No.	Capacity (mL)	Grad. Increment (mL)	ASTM Tol. (± mL)	Approx. O.D. x Height (mm)	Qty/Pk	Qty/Cs
1-3022-100	100	1.0	1.0	29 x 254	1	12
1-3022-250	250	2.0	2.0	39 x 340	1	12

## Biochemical Oxygen Demand Bottle



### Corning® Biochemical Oxygen Demand (BOD) Testing Bottle and Stopper

BOD bottles are suitable for incubating diluted samples of sewage, sewage effluents, polluted waters, and industrial wastes to determine the amount of oxygen required during the stabilization of the decomposable organic matter by aerobic biochemical action.

Cat. No.	Approx. Capacity (mL)	Stopper No.	Approx. O.D. x Height (mm)	Qty/Pk	Qty/Cs
1-1510-300	300	19 DBO	69 x 143	6	24

## Beaker



### PYREX Beaker, Low Form, Double Scale, Graduated

Cat. No.	Approx. Capacity (mL)	Graduation Range (mL)	Approx. O.D. x Height (mm)	Graduation Increment (mL)	Qty/Pk	Qty/Cs
1-1000-250	250	25-200	68 x 90	25	12	48

# Centrifugation and Storage



## Corning® 15 mL Centrifuge Tubes

Cat. No.	Description	Material	Cap Style	Max. RCF	Qty/Pk	Qty/Cs
83-430052	Conical bottom	PP	Plug seal	12,000	50/rack	500
83-430766	Conical bottom	PP	Plug seal	12,000	50/sleeve	500
83-430790	Conical bottom	PP	CentriStar™	12,500	50/rack	500
83-430791	Conical bottom	PP	CentriStar	12,500	50/sleeve	500

## Corning 50 mL Centrifuge Tubes

Cat. No.	Description	Material	Cap Style	Max. RCF	Qty/Pk	Qty/Cs
83-430897	Self-standing bottom	PP	Plug seal	3,000	25/sleeve	500
83-430921	Self-standing bottom	PP	CentriStar	3,000	25/sleeve	500
83-430290	Conical bottom	PP	Plug seal	15,500	25/rack	500
83-430291	Conical bottom	PP	Plug seal	15,500	25/sleeve	500
83-430828	Conical bottom	PP	CentriStar	17,000	25/rack	500
83-430829	Conical bottom	PP	CentriStar	17,000	25/sleeve	500

## Corning 250 mL and 500 mL Premium Quality Centrifuge Tubes and Support Cushions

Cat. No.	Description	Material	Cap Style	Max RCF	Qty/Pk	Qty/Cs
83-430776	250 mL Tube	PP	Plug seal	6,000	6	102
83-430236	250 mL Support cushion*	PEI	N/A	N/A	N/A	6
83-431123	500 mL Tube	PP	Plug seal	6,000	6	36
83-431124	500 mL Support cushion*	PEI	N/A	N/A	N/A	6

\*Support cushions must be used with the 250 mL and 500 mL centrifuge tubes unless the rotor has appropriately shaped V-bottom holders. PP = Polypropylene, RCF = Relative Centrifugal Force (x g), PEI = Polyetherimide

## Axygen® SnapLock Microcentrifuge Tubes

### 0.6 mL, Homopolymer

Cat. No.	Surface	Color	Packaging	Qty/Pk	Qty/Cs
383-MCT-060-C	Standard	MaxyClear	Bulk	1,000	10
383-MCT-060-B	Standard	Blue	Bulk	1,000	10
383-MCT-060-G	Standard	Green	Bulk	1,000	10
383-MCT-060-O	Standard	Orange	Bulk	1,000	10
383-MCT-060-R	Standard	Red	Bulk	1,000	10
383-MCT-060-V	Standard	Violet	Bulk	1,000	10
383-MCT-060-X	Standard	Amber	Bulk	1,000	10

### 1.5 mL, Homopolymer

383-MCT-150-C	Standard	MaxyClear	Bulk	500	10
383-MCT-150-B	Standard	Blue	Bulk	500	10
383-MCT-150-G	Standard	Green	Bulk	500	10
383-MCT-150-O	Standard	Orange	Bulk	500	10
383-MCT-150-R	Standard	Red	Bulk	500	10
383-MCT-150-V	Standard	Violet	Bulk	500	10
383-MCT-150-X	Standard	Amber	Bulk	500	10

### 2.0 mL, Homopolymer

383-MCT-200-C	Standard	MaxyClear	Bulk	500	10
383-MCT-200-B	Standard	Blue	Bulk	500	10
383-MCT-200-G	Standard	Green	Bulk	500	10
383-MCT-200-O	Standard	Orange	Bulk	500	10
383-MCT-200-V	Standard	Violet	Bulk	500	10
383-MCT-200-X	Standard	Amber	Bulk	500	10





### Axygen® SnapLock Microcentrifuge Tubes

#### 5.0 mL, Homopolymer

Cat. No.	Volume	Material	Color	Packaging	Quantity
383-MCT-500-C	5.0 mL	Homopolymer	Clear	Bulk	250/pk, 5 pk/cs
383-MCT-500-X	5.0 mL	Homopolymer	Amber	Bulk	250/pk, 5 pk/cs



### Axygen Microcentrifuge Tubes with Screw Cap

Cat. No.	Volume (mL)	Style	Color	Packaging
383-SCT-050-SS-C-S0.5	0.5	Self-standing, sterile	Clear	100/bag, 5 bags/pk, 8 pk/cs
383-SCT-150-SS-C-S1.5	1.5	Self-standing, sterile	Clear	100/bag, 5 bags/pk, 8 pk/cs
383-SCT-200-SS-C-S2.0	2.0	Self-standing, sterile	Clear	100/bag, 5 bags/pk, 8 pk/cs

Colored-cap versions are also available in sterile format.



## Additional Glassware



**PYREX® 2.4L Desiccator, Small Knob Top**

Cat No.	Description	Approx. I.D. of Ground Flange (mm)	Approx. Chamber Depth (mm)	Approx. Height (mm)	Plate Diameter (mm)	Qty/Cs
1-3081-150	Complete	172	81	252	140	1




**PYREX Fritted Disc, Gooch Type, High Form**

Cat. No.	Approx. Capacity (mL) and Porosity	Approx. Disc O.D. (mm)	Approx. O.D. x Height (mm)	Qty/Cs
1-32940-50M	50M	40	45 x 60	9



**PYREX Apparatus, Distilling, Kjeldahl, Nitrogen, § Joints**

Cat. No.	Description	Approx. Capacity (mL)	Qty/Cs
1-3340-500	Complete	500	1



**PYREX Funnel, Fluted, 60° Angle, Short Stem**

Cat. No.	Approx. Top I.D. (mm)	Approx. Stem Length x O.D. (mm)	Approx. Overall Length (mm)	Qty/Pk	Qty/Cs
1-6180-65	65	65 x 8	121	12	48




**PYREX Buret, Colored Scale, Class A, § PTFE Stopcock Plug**

Cat. No.	Approx. Capacity (mL)	Grad. Increment (mL)	Tol. (± mL)	Approx. O.D. x Height (mm)	Qty/Cs
1-2103-50	50	.10	.05	14 x 750	1




# Petri Dishes



## PYREX® Dish, Culture, Petri


Cat. No.	Description	Size (mm)	Approx. O.D. x Height (mm)	Qty/Pk	Qty/Cs
1-3160-100	Complete	100 x 10	100 x 14	12	72



## Corning® Gosselin™ Petri Dishes

### Petri Dish, 60 mm x 15 mm (D x H)

Cat. No.	Vents	Sterile	Units/Sleeve	Sleeves	Outer Bag	Qty/Cs
83-BP53-03	6	Yes	15	108	2	1,620



### Petri Dish, 150 mm x 15 mm (D x H)

Cat. No.	Vents	Sterile	Units/Sleeve	Sleeves	Outer Bag	Qty/Cs
83-BP143-06	3	Yes	11	16	2	176



# Inoculating Loops

## Corning® Gosselin™ Inoculating Loops

### PS Inoculating Loops – Needle Extremity

Cat. No.	Volume (µL)	Length (mm)	Color	Sterile	Pcs/Bag	Pcs/Box	Qty/Cs
83-OS1-01	1	192	Crystal green	Yes	20	150 x 3	9,000
83-OS10-02	10	194	Crystal blue	Yes	20	150 x 3	9,000



Needle Extremity – 1 µL



Needle Extremity – 10 µL

# Autoclave Bags

## Corning® Gosselin™ Autoclave Bags



### Transparent Autoclave Bags

Cat. No.	Volume (mL)	Height (mm)	Length (mm)	Thermal Resistance	Qty/Cs
83-SA03-01	3,000	400	255	134°C - 273°C	500
83-SA09-01	9,000	500	300	134°C - 273°C	500
83-SA14-01	14,000	600	400	134°C - 273°C	500
83-SA21-01	21,000	780	400	134°C - 273°C	500
83-SA33-01	33,000	780	600	134°C - 273°C	500



### Biohazard Logo Printed Autoclave Bags

Cat. No.	Volume (mL)	Height (mm)	Length (mm)	Thermal Resistance	Qty/Cs
83-SA03-10	3,000	400	255	134°C - 273°C	500
83-SA09-10	9,000	500	300	134°C - 273°C	500
83-SA14-10	14,000	600	400	134°C - 273°C	500
83-SA21-10	21,000	780	400	134°C - 273°C	500
83-SA33-10	33,000	780	600	134°C - 273°C	500

**For purchases from April 1, 2020 through December 31, 2020**

**To purchase your qualifying products and redeem this promotion:**

1. Purchase the qualifying Water Testing products
2. Redeem Free Water Testing products equal to 25% of your total purchase from items in the Corning Water Testing Product Selection Guide by:
  - ▶ Sending an email to your local Corning Account Manager. To locate your local Account Manager, contact Customer Service at 800.492.1110 or CLSCustServ@corning.com.
  - ▶ Put promotional code “**PRO-25 WATER TESTING-20**” in the subject line and provide the following information in the body of the email:
    - Your name, phone number, organization, and shipping address (including Bldg/Lab/Room)
    - Corning Cat. No. of free goods
    - Attach proof of purchase (purchase order)

**Terms and Conditions:** Offer valid in the U.S. only and void where prohibited by government, law, or company policy. Offer valid for end-user customers only for purchases from April 1 through December 31, 2020 or while supply lasts. Redemption information must be received by January 15, 2021. Corning has the right to substitute products if required. Please allow 4-6 weeks for delivery.

For more specific information on claims, visit the Certificates page at [www.corning.com/lifesciences](http://www.corning.com/lifesciences).

**Warranty/Disclaimer:** Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Not for use in humans.

**CORNING**

**Corning Incorporated**  
*Life Sciences*

836 North St.  
Building 300, Suite 3401  
Tewksbury, MA 01876  
t 800.492.1110  
t 978.442.2200  
f 978.442.2476  
[www.corning.com/lifesciences](http://www.corning.com/lifesciences)

For additional product or technical information, visit [www.corning.com/lifesciences](http://www.corning.com/lifesciences) or call 800.492.1110. Outside the United States, call +1.978.442.2200 or contact your local Corning sales office.

For a listing of trademarks, visit [www.corning.com/clstrademarks](http://www.corning.com/clstrademarks). All other trademarks are the property of their respective owners.